



## TECHNICAL DATA DECOR FINISH

Issued on 15/09/2015 - Rev. n. 1 of 09.15.2015

### Description:

Shining transparent acrylic paint water-component, water-resistant. Protecting and decorating floors and walls in 3D and Cement walls in Stonehenge.

### Application:

transparent painting, decorative sector, specifically for the protection of walls and floors such as in 3D Cement; shops, warehouses, hospitals, bars, restaurants, mechanical, pharmaceutical and food, private homes etc ...

### Surface preparation:

The surface of the 3D Cement must be dry, free from dust and anything else that could impair the perfect adhesion of the product.

### Preparation of the product:

Decor Finish is ready to use, mix thoroughly before application.

### Product Application:

Decor Finish can be applied by roller, brush, spray gun in two hands or three coats spaced 6/8 hours of each other, said times are greatly influenced by temperature and ventilation during drying; variations of these parameters, may make it necessary to lengthen the drying time. In case of insufficient respect of the drying time, the applied product could wrinkle, crack, forming strips or rise.

### Features:

- Excellent surface finish
- Waterproof and dustproof
- Easy to wash
- It resists abrasion
- Drive over, resists forklift traffic
- Consolidating
- Exempt from organic solvents
- Applicable indoors, odorless
- versatile product, adheres on every surface
- Resistant to thermal shock
- It requires minimal maintenance even after many years
- Easy application
- The product is formulated with low environmental impact

### Technical data:

- Practical Coverage: 10 m<sup>2</sup> to 2.5 liters with two hands, according to variable absorption and roughness of 3D Cement
- Specific Gravity 1.0 ± 0.05 at 20 ° C.
- Color: Transparent
- Resistance to temperature: Operating temperature up to 70 ° C

- Packaging: Lt 2.5
- Conservation in its original sealed packaging and in a dry place between + 5 ° C and + 30 ° C. one year
- The complete drying and the achievement of maximum chemical and mechanical resistance is obtained in at least seven days, variable depending on the thickness and temperature. During the drying process promote the exchange of air.
- Security (for EEC legislation):
- The product is not flammable or hazardous
- Safety: no subject
- Risk phrases: not subject
- Symbols: no subject
- The product does not require labeling in accordance with Decree Law N ° 65 of 14/03/2003 and subsequent changes and updates.

Background notes:

- As for information about proper disposal, storage and handling of the product, please refer to the Material Safety Data Sheet.
- All technical information contained herein are indicative.
- For more detailed information please consult our TECHNICAL ASSISTANCE service.

The data and information contained in this technical data sheet are based on the best practical and laboratory testing, but should be regarded as indicative. Considering the different conditions of use, and the intervention of independent factors from Nikkolor Italy (support, environmental conditions, technical direction of installation, etc.) Who intends to make use of it is required to determine whether the product is suitable or not for use. The ns. warranty obligation is therefore limited to the quality and consistency of the same relatively to the finished product, and exclusively for the above data. The data may vary at any time without prior notice from the Nikkolor Italy. Updates will be posted on the site [www.nikkolor.net](http://www.nikkolor.net)